



JOHNSON PUMP
AN SPX BRAND



Viking Compact

Full-capacity, hand-powered bilge pump

When you need to bail water from the bilge at sea, you need to be able to rely on the pump at hand. Thanks to the Viking Compact manual bilge pump's well considered design, bailing has never been easier. Perfect for installation in tight spaces, the Viking Compact can be mounted wherever it's most appropriate.

No one knows boat pumps better than the engineers at SPX Johnson Pump Marine. Their latest work is the new Viking Compact manual bilge pump, which combines the best aspects of simplicity, reliability and modern industrial design.

This rugged, yet sleekly designed, single-chamber diaphragm pump provides first-rate performance and is a snap to install. It can be fitted in minutes from one side of the bulkhead with just four screws, self-sealing against the surface with a durable, watertight gasket.

With the pump house recessed behind the bulkhead, only the handle is visible from the cabin or cockpit. The well-proven diaphragm design provides high pumping capacity, ensures easy pumping action and complies with ISO 15083 safety requirements.

The Viking Compact's inlet and outlet ports can be swiveled 360° and are delivered in two sizes with every pump, Ø25mm (1") and Ø38mm (1.1/2"). Naturally, the Viking Compact has KlickTite™ connectors fitted as standard, literally making hose connections a snap!

Features

- Quick to install from one side of the bulkhead
- Fits industry standard aperture, even in tight spaces
- Robust pump handle and cover in-one
- Self-priming for immediate effect
- 3.3 meter (10'8") combined lift/head
- Easy, low-cost, low-frequency maintenance
- Durable gasket for tight fit against the bulkhead
- Rattle-free design
- Polypropylene body
- All metal parts made of stainless steel
- Easy pump-action, single diaphragm design
- KlickTite™ port connectors standard
- Hose connectors can be turned in any direction
- Heavy duty non-choke valves throughout
- High flow tricuspid valve on the outlet port
- Complies with ISO 15083

*Dependability in the
grasp of your hand!*

SPX®

Technical specifications, Viking Compact

Body	Polypropylene
Cover	ABS
Diaphragm	Nitrile rubber
Valves	Nitrile rubber (1 leaf and 1 tricuspid valve)
Wetted parts	Polypropylene, PA66GF30 plastics and nitrile rubber
Maximum lift	2.1 meters (7 feet)
Maximum head	1.2 meters (4 feet)
Combined head/lift	3.3 meters (10.8 feet)
Connection	KlickTite™ connectors for 1" (25mm) or 1.1/2" (38mm) hose; both options included
Max. liquid temp	+60°C (140°F)
Weight	0.675 kg (1.5 pounds)

Flow at 10 kPa head and 45 strokes/min

Ø25mm connections 34,5 liters/minute (9.1 US gallons/minute)

Ø38mm connections 45 liters/minute (11.9 US gallons/minute)

Order No.	Description
10-24800-01	Viking Compact w. dia. 25 mm (1") and dia. 38 mm (1½") ports. Consumer pack
10-24800-10	Viking Compact w. dia. 38 mm (1½") ports Bulk pack.
10-24800-11	Viking Compact w. dia. 25 mm (1") ports Bulk pack.
10-24800-12	Viking Compact w. dia. 38 mm (1½") ports and 25 mm (1") ports. Bulk pack



SPX Johnson Pump Marine AB
Nastagatan 19, P.O. Box 1436
SE-701 14 Örebro, Sweden
Phone: +46 (0)19 21 83 00 Fax: +46 (0)19 27 23 72
E-mail: johnson-pump.marine@processequipment.spx.com

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.johnson-pump.com or www.spxe.com. SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation. Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 04/2009 JP-126

Copyright © 2009 SPX Corporation

SPX®

PROCESS EQUIPMENT